









| compatible models | | | ATX 330EH/EDH ATX 340EH/EDH | | rear column tail lift | | |
|---|--------|--------|--------------------------------|----------------------------------|--|---------------|---------------|
| N1 road homologation | | | • | | swinging and folding aluminium platform | | |
| model | | length | height | tail lift module | mounted on 2.000 mm x 1.400 mm dropside body with: | | |
| ATX 330EH | [mm] | 3.730 | 1.980 (with standard tyres) | | | | |
| ATX 330EDH | [mm] | 4.490 | | mesh sides extension F | | 155 CM [mm] | 1.820 x 1.260 |
| ATX 340EH | [mm] | 3.730 | | module: length | | [mm] | 1.400 |
| ATX 340EDH | [mm] | 4.490 | | module: weight | | [kg] | 370 |
| width of vehicle (with wing mirrors closed / open) [mm] | | | 1.380 / 1.650 | module: platform's load capacity | | [kg] | 500 |
| loading capacity of vehicle is given by the load capacity (chassis) of the model on which is mounted the module less the weight of the module and optionals/accessories | | | | module: platform's length [mm] | | _ | 1.300 |

- · as standard
- ! compatible but not type-approved for road circulation
- $\Delta \quad \text{optional} \quad$ not available



amber LED beacon light mounted on top of the cab

· as standard

not available

 $\Delta \quad \text{optional} \quad$



Δ



optionals and accessories external pushbutton for outboard operations

NOTE

This module is powered by the battery of the vehicle therefore can affect the autonomy

For all the other data refer to the technical specs of the model on which is fitted the

module. The technical specifications, design and performance of the products listed in this technical sheet are indicative and may undergo modifications without forewarning.



| | |
|----------------------------|-------|
| Via Cile, 5 35127 Padua | Italy |





| www | | www.alke.com |
|-----|--|--------------|
|-----|--|--------------|







! compatible but not type-approved for road circulation

© 2019 Alkè

Rev. 190204



The technical specifications, design and performance levels indicated in this technical data sheet are by way of example only and may be subject to modifications without prior notice.